

Mini Vans Bone Stock Rules:

-Promoted by Oklahoma boys Promotions L.L.C.-

General Rules and Regulations:

IF IT DOESN'T SAY YOU CAN DO IT IN THESE RULES DON'T!!!

1. Vans shall be mini vans front wheel drive, no full size vans and no full frame or flat nose vans. 4 x 4 and all wheel drive must remove one drive line.
2. All driver's must sign driver's paperwork before being inspected or they will not run.
3. Driver's must wear a seat belt, helmet, long sleeve shirt, pants (Fire Suit highly recommended).
4. All drivers must attend the pit meeting before the event.
5. No drivers are allowed any alcohol or drugs before the event, If found under the influence while wearing a drivers band you will be disqualified for the remainder of the event.
6. Any complaints that a driver has about another car prior to the start of your heat will need to be addressed in the drivers meeting in specifics. If nothing is said, we don't want to hear about it after the show.
7. **DO NOT** paint anywhere on suspension, frame or interior of car.
8. **Judges decisions are final!!**

Show Rules:

1. **You have 1 minute to make an aggressive hit, After 1 minute that car is disqualified.**
2. For safety, **DO NOT HIT IN THE DRIVER'S DOOR!!**
3. You will be given 2 fires 1st one we put out and the 2nd one you are done for that round.
4. Rollovers, you may keep going as long as car is deemed safe.
5. No holding or pinning, you must back up and show day light. You may not pin to win

Car Preparation:

1. No fresh paint or undercoating on the frames at all. No buffing or grinding frames or bodies except where welding is specifically allowed in the rules.
2. All cars must be stock, unless modification is stated in the rules.
3. All glass, plastic, chrome, and interior must be removed from the car before arriving to the derby.
4. All trailer hitches and braces must be removed.
5. You **MUST** have a number in bright colors on each front door and may have a sign on the roof of your car with car number on it for recognition or car.
6. Batteries must be moved to passenger front floorboard. They must be properly secured and covered.

7. All cars must have working brakes, If the car is not able to exhibit the ability to stop, it will not be inspected.
8. **NO** welding other than what is mentioned in this set of rules. If your car is found with any weld other than what is allowed and you refuse to fix it to the judges satisfaction, you and your car will not run.

Body:

1. Remove all glass mirrors and plastic. Remove all decking in wagons, cars must be swept clean of all debris before you get to the derby.
2. **No sedagons** fresh or preran, zero crease enhancement, zero sheet metal or frame shaping, forming or folding.
3. Fasten tailgate with 4 places 2 strands of #9 wire or 3/8" chain.
4. Anything can be removed, Nothing can be added.
5. Hoods get one hood clip 3" long 2"x 2" x3/16" with one 1/2" bolt and nut per side. (2) 5/8" bolts total thru hood in firewall area and 2 core support bolts thru the hood to top of frame only with 4" washes.
6. You may weld doors total of 6 inches on each vertical seem only 2"x 1/8" strap. Drivers door may be welded solid.
7. Body mounts and spacers to remain stock and in place. If they are broken or rusted out, a single piece #9 wire may be substituted. No body bolt changing allowed.
8. #9 wire, chain or bar required in front windshield.
9. Fenders may be trimmed.

Frames

1. No welding on frames allowed.
2. No suspension modifications allowed, must remain strictly stock.

Tires/wheels:

1. Tires no bigger than 16 inches, no split rims, no studded tire, Doubled tires are ok No foam filled.

Driver's Compartment:

1. 4-point square cage with one 2 x 3 down tube to sheet metal only per side. Halo bar allowed to back seat bar or floor sheet metal. Gas tank must be mounted horizontally and 8 inches off floor. No gas tank protectors.
2. Driver's door must be padded.
3. Gas tank and battery must be moved and secured. Tank behind seat and battery centered in passenger front floorboard.
4. Trans coolers allowed, must be mounted inside of cage area.

Bumpers:

1. You may weld on any stock bumper with 4" x 4" x ¼" plate on out side of frame. Bumpers may be trimmed.